

# ACS

# 銀箭牌

## Automatic Circular Collar Attaching Device

## 自动上圆领装置



在气动导布与滚轮撑开的基础上，加上自动顺布条，接缝骨自动定位，节省90%的上料时间。

Based on pneumatic tape guide and tubular extending roller set, with advanced function as automatic tape alignment, automatic joint-seam positioning, which save 90% material loading time.



# 特点

# FEATURES

- 1** 自动侦测缝骨位置，减少工人对位时间。  
Auto detect and position the collar-seam by sensor. It saves the time to find the collar-seam for aligning with clothes body.
- 3** 导布结构，缝合衣领与布身时，防止偏斜。  
Equipped with fabric guider to ensure a quality alignment between collar and clothes body.
- 2** 可调式张力控制机构，减少布料起皱现象。  
Tubular tension control system avoids puckering.
- 4** 电眼控制导布装置自动开合。  
Fabric guider movement is automatically controlled by sensor.



# 规格

# SPECIFICATIONS

型号 Model	ACS200	领围车缝范围 Applicable Collar Circumference	<p>拉伸後领围 38-80 cm Stretch Applicable Collar Circumference</p> <p>领高 1.5~3 cm Applicable Collar Height</p>
搭配缝纫机机头 Machine Head	747KST-514M-3-24/VT		
车缝速度 Sewing Speed	4500 SPM (最高 Max)	领高车缝范围 Applicable Collar Height	
使用布料 Type of Fabric	弹性布料 Elastic fabric	电源电压 Power Supply	Single Phase 1Φ AC200~240V 50/60Hz
布厚车缝范围 Applicable Cloth Thickness	对折後 1.2 mm ±0.2 mm After fold 1.2 mm ±0.2 mm	电力消耗 Power Consumption	650 W (Max)
气体消耗量 Air Consumption	150 公升 / 分 150 L/min	生产效率 Production Capacity	车缝速度：4000 SPM、车缝时间：180-240 件 / 小时 Sewing speed: 4000 SPM、Cycle time: 180-240 pcs / Hr
气压 Air Pressure	0.5 MPa		



高林股份有限公司  
KAULIN MFG. CO., LTD.

由於对产品的改良及更新，本产品型录中之产品规格及外观的修改恕不事先通知！  
The specification and/or appearances of the equipment described in this catalogue are subject to change without previous notice because of modification.

C.S2023-26. AUG. 2023