



NC008

针送牛仔裤腰车
Needle Feed Cylinder Bed Double
Chainstitch Machine for Jeans Waistband



You Tube



YOUKU



产品特点 / FEATURES

1 後拉轮能在高速车缝时让送布均匀，线迹美观
Rear puller allows stable material feeding and well-balanced seam.

3 可对应至16oz的丹宁布等重厚型布料
Work on heavy material like Denim, up to 16 oz.

2 可同步调整线迹长度与送布量的针送+下送送布机构
Needle feed and material feed can be adjusted synchronously.

4 最适合车缝牛仔裤腰，也可应用于牛仔裤的约克、卷边缝、门襟车缝，上松紧带
Designed for jeans waistband sewing, also can apply on jeans yoke seam, front, and elastic attaching.

配件 / DEVICE



HPR / 裤头上带滚边车缝
适用于厚料工作裤，牛仔裤的上带滚边一次成型车缝左右分开的下轮可用转弯缝制，可依样式选择喇叭。

HPR/WAISTBAND ATTACHING DEVICE
For tape binding on waistband of workwear pants, jeans...etc.
Refer to below table to find optional binders for desirable seams.



JD / 跳针装置
避开裤腰车缝时不需下针的地方。

Skip Stitch Device
Control freely to avoid stitches sewed on unwanted working area.

选配喇叭 / OPTIONAL BINDER

成品尺寸 (Finished Size)	上下片直送 For Continuous Strips	上下片弧形 For Arched Type	侧送喇叭 Side Feeding	前送喇叭 Front Feeding
1- 3/8" (36mm)	B516P	B518P	B519P	B530R
1- 1/2" (38mm)	B516Q	B518Q	B519Q	B530S
1- 5/8" (42mm)	B516R	B518R	B519R	B530T
1- 3/4" (45mm)	B516S	B518S	B519S	B530U
缝合样式 Seam Type				

规格 / SPECIFICATION

NCO08				mm 		Needle No.	
NC008-02318	2	4	5/4" (31.75mm)	1.4~3.6	9	DXV57 #14~#25	4000
NC008-02381	2	4	3/2" (38.1mm)	1.4~3.6	9	DXV57 #14~#25	4000
NC008-0464-254	4	8	1/4-1-1/4" (6.4-25.4-6.4mm)	1.4~3.6	9	DXV57 #14~#25	4000
NC008-04254	4	8	1" (25.4mm)	1.4~3.6	9	DXV57 #14~#25	4000
NC008-0464-254/HPR	4	8	1/4-1-1/4" (6.4-25.4-6.4mm)	1.4~3.6	9	DXV57 #14~#25	4000
NC008-0464-222/HPR	4	8	1/4-7/8-1/4" (6.4-22.2-6.4mm)	1.4~3.6	9	DXV57 #14~#25	4000
NC008-06064	6	12	1/4" (6.4mm)	1.4~3.6	9	DXV57 #14~#25	4000

高林股份有限公司
KAULIN MFG. CO., LTD.

由於对产品的改良及更新，本产品型录中之产品规格及外观的修改恕不事先通知
The specification and/or appearances of the equipment described in this catalogue are subject to change without previous notice because of modification.

C.S2023-13. JUL. 2023